



Technical Data Sheet

POLYESTER CORDED STRAPPING COMPOSITE QUALITY

Type	CS19ST
Width	19 mm (+0,20mm/-0,80mm)
Length of coil	600 m / 700 m (+/-1%)
Linear Breaking strength	Avg. 500 daN (+/- 7%)
System Strength with CB6 Buckle (4,00mm Galvanized Wire diameter)	Avg. 800 daN Kg (+/- 7%)
Elongation at break	12 % (+/- 3%)
Raw material	High tenacity polyester fiber Polypropylene-coating Homopolymer 100% virgin material
Temperature range	Max. 120° C
Inside diameter of coil	200 mm
Width of coil	190 mm (approx.)
Outside diameter of coil	380 mm (max.)
Packaging	2 coils per carton - 90 coils per pallet 114 x 114 cm 2 coils per carton – 60 coils per pallet 80 x 120 cm
Weight	8,30 kg per coil / 600m (approx.) 9,70 kg per coil / 700m (approx.)

Head Office / Factory

TT Endüstriyel Ambalaj Makine Sanayi ve Ticaret A.Ş. Tekirdag, Turkey

CO-STRAP Verpackungslösungen GmbH

Company: 91541 Rothenburg ob der Tauber, Germany

Warehouse: 63526 Erlensee, Germany

